REQUIRED BUILDING INSPECTIONS

(Residential New Construction)

Veenstra & Kimm Engineering

3000 Westown Parkway West Des Moines, IA 50266-1320 515 225-8000

Permit required to be posted at front of structure on a post until it can be attached inside garage area.

Portable Toilet, posted house numbers and dumpster required on job sites.

| FootingsPrior to pouring concrete, after forms and rods. |
|--|
| Footing WallsPrior to pouring concrete, non centered uprights tied to center. |
| Deck post holesPrior to pouring, at least 42" deep (if attached to house.) |
| Electrical Temp PoleNo Inspection needed. |
| Tar Tile GravelPrior to Backfill (may be inspected during plumbing ground work) |
| Sewer/Storm/WaterDrainage pipe with 5ft head, gravel bed, Tracer wire on PEX. |
| Groundwork5ft head wet test or air test, gravel bed, staked down. |
| Shear Wall Nails Every 3", #8s. including sill plate. Straps on headers. (Will inspect during framing) |
| Plumbing RoughPrior to insulation, wet test 5ft head or air test 5psi. Pex, air or water test. |
| Electrical RoughPrior to insulation, Ground, Panel & Meter box installed |
| HVAC RoughPrior to insulation |
| Framing RoughPrior to insulation, after all mechanicals roughed in.* |
| InsulationPrior to drywall. No VK inspection needed if Performance test is done. (Send us the data before Final please) |
| Sidewalk & ApproachPrior to pouring concrete, granular compacted gravel. Stop Box cap sleeved with metal. |
| Final Structure may not be occupied until final inspection and Certificate of Occupancy has been issued. |

Call V&K at 515 225-8000 to schedule an inspection Inspections are between 8:00 and 4:30pm M-F

Note: City of Bondurant requires water meter set before rough-in inspections. Check with City Hall.

Temporary safety railings are required around open stairwells before mechanicals are installed!

As of January 1st 2016 most cities will have adopted the 2015 IRC & IBC Building Codes, IPC Plumbing code and 2014 NEC. (State of Iowa inspects Electrical for cities listed below with an asterisk*).